

ZI-HS22EZ

log splitter



- vertical design for splitting logs up to 1100 mm length
- slow and fast forward speed
- operation possible via integrated electric motor or PTO shaft
- PTO 3-point hitch for transportation (cat 1)
- stable and torsion-resistant steel construction
- stepless adjustable split lift for a fast and convenient handling
- state-of-the-art safety controls according to the new 2017 standard
- including log lift
- convenient transport due to integrated moving device



**YOUR
JOB.
OUR
TOOLS.**

ZI-HS22EZ

log splitter



technical details

motor power s6 in W	5100 (40%)
total dimensions in mm	1050x1700x2500
splitting blade stroke in mm	948
log splitting capacity	560-1100
hydraulic lift in MPa	24,73
reverse speed in cm/s	7,5
handgrip vibration in m/s ²	<2,5
net weight in kg	320
packaging length in mm	940
EAN code	9120039233703

voltage	400V 50Hz
splitting force in t	22
splitting diameter in mm	80-350
hydraulic oil capacity in l	24
forward speed in cm/s	4,3 / 10,5
sound pressure level in dB(A)	<80
gross weight in kg	332,900
packaging width in mm	680
packaging height in mm	2.000

**YOUR
JOB.
OUR
TOOLS.**